Technical Data Sheet

DENSUS A3/B4 5W-40

Motor oil for passenger cars

Description

Modern synthetic universal motor oil based on selected synthetic base oils and advanced additives. It provides a high and stable viscosity index, shear stability, fast cold start, oxidation resistance, a reliable high-temperature oil film, detergency/dispersancy and strong wear/corrosion protection.

Specifications

ACEA A3/B4; API SN/CF; MB 229.3 / 226.5; Renault RN0700 / RN0710; VW 502.00 / 505.00; BMW Longlife-01; Fiat 9.55535-M2; GM LL-B-025; Porsche A40; PSA B71 2296

Typical characteristics

Test	Method	Unit	Average results
Density at 15°C		kg/l	0,853
Viscosity at -30°C		mPa.s	5880
Viscosity at 40°C		mm²/s	92,20
Viscosity at 100°C		mm²/s	14,70
Viscosity index			167
Flash Point COC		°C	228
Pour point		°C	-42
Total Base Number		mgKOH/g	10,8
Sulphate Ash		%	1,32

Applications

Recommended for petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans where the listed performance levels are required.

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions

ELOI OIL LLP
Ormond House, 26/27 Boswell Street, Suite 2
London, England, United Kingdom, WC1N 3JZ
E-mail: sales@eloi-oil.uk
www.eloi-oil.uk