Technical Data Sheet

ELATUS C3 5W-40

Premium mid-SAPS engine oil

Description

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:; a lower fuel consumption a high and very stable viscosity index; a high resistance against shearing a very fast cold start; a very strong resistance against oxidation a safe lubrication film at very high temperatures; a very good detergency and dispersion a very strong protection against wear, corrosion and foaming.

Specifications

ACEA C3; API SN; BMW Longlife-04; MB 229.31/229.51/229.52; Porsche C40; VW 511.00; GM dexos 2; Renault RN0700/RN0710

Typical characteristics

Test	Method	Unit	Average results
Density at 15 °C		kg/l	0,848
Viscosity -30 °C		mPa.s	5690
Viscosity 40 °C		mm²/s	68,90
Viscosity 100 °C		mm²/s	12,70
Viscosity Index			187
Flash Point COC		°C	228
Pour Point		°C	-42
Total Base Number		mgKOH/g	7,7
Sulphate Ash		%	0,78

Applications

A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans. Specially developed for use with the specified specifications. Among others for: W12, V10, V8 and six-cylinder boxer engines; Audi, Bentley, Lamborghini and Porsche.

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions

ELOI OIL LLP
Ormond House, 26/27 Boswell Street, Suite 2
London, England, United Kingdom, WC1N 3JZ
E-mail: sales@eloi-oil.uk
www.eloi-oil.uk