Technical Data Sheet

ELATUS RC 10W-60

Premium performance engine oil

Description

A synthetic engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:; a very low tendency to evaporation a high and very stable viscosity index; a good resistance against shearing a high resistance against aging; a safe lubrication film at low and very high temperatures a very good detergency and dispersion power; a very strong protection against wear, corrosion and foaming.

Specifications

ACEA A3/B4; API SN/CF

Typical characteristics

Test	Method	Unit	Average results
Density at 15 °C		kg/l	0,859
Viscosity -25 °C		mPa.s	6050
Viscosity 40 °C		mm²/s	164,00
Viscosity 100 °C		mm²/s	23,10
Viscosity Index			170
Flash Point COC		°C	242
Pour Point		°C	-45
Total Base Number		mgKOH/g	10,3
Sulphate Ash		%	1,09
HTHS		mPa.s	5,56
Noack		%	4,8

Applications

A synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions

ELOI OIL LLP
Ormond House, 26/27 Boswell Street, Suite 2
London, England, United Kingdom, WC1N 3JZ
E-mail: sales@eloi-oil.uk
www.eloi-oil.uk